








PVC MEMBRANE COLOR SELECTION AND RATING GUIDE




WHITE	50mil	60mil ●	80mil
Solar Reflectance Thermal Emittance SRI Value Initial SRI Value 3-Year Aged LRV	d	(0.870 0.88 110 91 94.3


*Available in Fleeceback and ChemGuard




BROWN 50m	0 •
Solar Reflectance	0.079
Thermal Emittance	0.87
SRI Value Initial	2
SRI Value 3-Year Aged	N/A
LRV	7.2




COOL STONE	50mil	60mil	80mil
	O	●	O
Solar Reflectance Thermal Emittance SRI Value Initial SRI Value 3-Year Age LRV	d		0.77 0.63 95 75 N/A




RED	50mil O	60mil O	80mil
Solar Reflectance Thermal Emittance SRI Value Initial SRI Value 3-Year Age LRV	d	(0.243 0.88 25 N/A 9.7




COOL SAND	50mil	60mil	80mil
	O	●	O
Solar Reflectance Thermal Emittance SRI Value Initial SRI Value 3-Year Age LRV	ed		0.77 0.87 95 78 69.7



GREEN	50mil O	60mil O	80mil
Solar Reflectance		(0.073
Thermal Emittance			0.88
SRI Value Initial			2
SRI Value 3-Year Aged	d		N/A
LRV			7.7



TAN	50mil ●	60mil ●	80mil
Solar Reflectance Thermal Emittance SRI Value Initial SRI Value 3-Year Age LRV	ed .	(0.366 0.87 39 N/A 30.2



GRAY	50mil	60mil ●	80mil
Solar Reflectance		C	0.163
Thermal Emittance			88.0
SRI Value Initial			13
SRI Value 3-Year Aged	t		N/A
LRV			18.1

For more information about IB membrane specifications and details please visit IBroof.com. Colors as shown are for illustration purposes. Please refer to an actual sample for full color consideration. Request a sample online at www.IBroof.com/samples-and-literature/

Rev.07.19

























